UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/007,175	10/23/2001	Keijiro Watabe	01650/LH	5677

1933   7590   05/04/2005

FRISHAUF, HOLTZ, GOODMAN & CHICK, PC
767 THIRD AVENUE
25TH FLOOR
NEW YORK, NY 10017-2023

EXAMINER
MISLEH, JUSTIN P

ART UNIT	PAPER NUMBER
2612	

DATE MAILED: 05/04/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

PTO-90C (Rev. 10/03)

	Application No.	Applicant(s)
Office Action Summary	10/007,175	WATABE ET AL.
	Examiner	Art Unit	
	Justin P. Misleh	2612	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) FROM
THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed
  after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any
  earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☒ Responsive to communication(s) filed on *17 January 2005*.

2a) ☒ This action is **FINAL**.   2b) ☐ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is
closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) *1 - 13* is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) *1 - 11* is/are rejected.

7) ☒ Claim(s) *12* is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☒ The specification is objected to by the Examiner.

10) ☒ The drawing(s) filed on *23 October 2001* is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☒ All   b) ☐ Some * c) ☐ None of:

      1. ☒ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage
application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
    Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____.

5) ☐ Notice of Informal Patent Application (PTO-152)

6) ☐ Other: _____.

DETAILED ACTION

Response to Arguments

1.   Applicant's arguments with respect to Claims 1, 6, and 13 have been considered but are

moot in view of the new grounds of rejection.

2.   In regards to Claims 2 and 8, the Applicant argues "estimates of traveling distance based

on pulses from encoder are often" and therefore, Gordon et al. does not at all disclose, teach or
                                     inaccurate
suggest the features recited in Claims 2 and 8.

        The incremental position encoder (194) is responsible for monitoring motor movement

by encoding motor rotations. The wheel moves by rotation as the motor drives by rotation.

Therefore, determining motor movement by encoding motor rotations directly corresponds to

measuring the length of a portion of a wheel, which has been brought into contact with the floor

surface. It is clear that Gordon et al. measures a length by means of an encoder and, furthermore,

the claim language does not specifically prevent an encoder from measuring a length.

3.   In regards to Claims 4 and 11, the Applicant argues "if three wheels at vertices of an

equilateral triangle are moving in a direction parallel to one of the equilateral triangle, then a

distance along the moving direction between the two wheels on the one side of the triangle is

greater than a distance between either one for the two on the one side of the triangle and the third

wheel.

        The Applicant is reminded that the space between three respective wheels placed at the

vertices of an equilateral triangle is equidistant. Thus, the space between the two wheels along a

moving direction of the triangle that is parallel to the one side of the triangle having the two

wheels is the same.

4.   Applicant's amendments to the specification and the drawings are accepted and approved

by the Examiner. All previous objections to the specification and the drawings are hereby

withdrawn. However, newly presented is an objection to the abstract (see below for details).

Abstract

5. .   Applicant is reminded of the proper language and format for an abstract of the disclosure.

The abstract should be in narrative form and generally limited to a single

paragraph on a separate sheet within the range of 50 to 150 words. It is important that the

abstract not exceed 150 words in length since the space provided for the abstract on the computer

tape used by the printer is limited. The form and legal phraseology often used in patent claims,

such as "means" and "said," should be avoided. **The abstract should describe the disclosure**

sufficiently to assist readers in deciding whether there is a need for consulting the full

patent text for details.

The language should be clear and concise and should not repeat information given in the

title. It should avoid using phrases which can be implied, such as, "The disclosure concerns,"

"The disclosure defined by this invention," "The disclosure describes," etc.

Appropriate correction is required.

Claim Rejections - 35 USC § 103

6.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in
> section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are
> such that the subject matter as a whole would have been obvious at the time the invention was made to a person
> having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the
> manner in which the invention was made.

7.   **Claims 1 – 11 and 13** are rejected under 35 U.S.C. 103(a) as being unpatentable over

Gordon et al. in view of Fellous.

8.   For **Claim 1**, Gordon et al. disclose, as shown in figures 1C, 2, 5A – 5F, 7, and 8 and as

stated in columns 4 (lines 10 – 64), 5 (lines 36 – 58), 6 (lines 31 – 37), 7 (lines 50 – 66), 10 (lines

39 – 68), 11 (lines 1 – 4), and 12 (lines 16 – 37), an image pick-up method for picking up an

image of an object with a camera mounted via a pan head on a moving pedestal, said method

comprising:

setting a reference position (initial encoder count from incremental position encoder 194)

on a floor surface on which the moving pedestal moves and a reference angle (initial encoder

count from wheel angle encoder 192) of the moving pedestal;

detecting a moving amount of the moving pedestal from said reference position and a

rotation angle of the moving pedestal from said reference angle (by means of the encoders 192

and 194);

finding a position and an angle of the camera with respect to the object based on said

reference position, said reference angle, said moving amount and said rotation angle (all of the

above factors are used by the microprocessor 180 to calculate a "position error signal" used to

produce an appropriate motor velocity for the motors of the moving pedestal); and

transmitting data of the position and the angle of the camera with respect to the object to

a computer for creating an image containing a real object image of the object taken with the

camera (see column 10, lines 64 – 68; column 11, lines 1 – 4; and column 12, lines 16 – 37).

Gordon et al. clearly disclose transmitting data of the position and the angle of the camera

with respect to the object to a computer for creating an image containing a real object image of

the object taken with the camera; however, Gordon et al. do not disclose an image pickup

method for operating together a real object image of an object taken with the camera and another

image or a computer for operating together the real object image of the object taken with the

camera and said another image based on the position and the angle of the camera with respect to

the object.

On the other hand, Fellous also disclose an image pick-up method for capturing images

of an object with a camera mounted on a moving pedestal. More specifically, Fellous teach, as

shown in figures 1 and 2 and as stated in columns 5 (lines 3 – 23, 31 – 49, and 59 – 67), 6 (lines

6 – 25, 34 – 39, and 49 – 53), 7 (lines 1 – 18), an image pick-up method for capturing images of

an object (24 and 13) with a camera (2) mounted on a moving pedestal (5) and for operating

together (via computer 11) a real object image ("real images generated by the camera 2") of an

object taken with the camera ("fine-lined rectangle 24") and another image ("synthetic image"

shown on monitor 12), wherein a computer (11) is provided for operating together ("create a

hybrid combined image" – see column 5, lines 18 – 27) the real object image ("real images") of

the object taken with the camera (2) and said another image ("synthetic images") based on the

position and the angle of the camera with respect to the object ("geometrical coherence" – see

column 6, line 54 – column 7, line 15).

As stated in column 2 (lines 1 – 25) of Fellous, at the time the invention was made, it would have been obvious to one with ordinary skill in the art to have provided a computer for operating together the real object image of the object taken with the camera and said another image based on the position and the angle of the camera with respect to the object as taught by Fellous, in the image pick-up method including a camera mounted on a pedestal disclosed by Gordon et al., for the following advantages: facilitating easy determination in a host computer of a parametric model of a real camera analogous to a virtual camera, providing real control of a virtual camera by a real camera, securing perfect coherence between a real image and a virtual image, and permitting a free combination of real images and geometrically coherent synthetic images.

9.   As for **Claim 2**, Gordon et al. disclose wherein said detection means detects the moving amount of the moving pedestal by measuring a length of a portion of a wheel of the moving pedestal, which has been brought into contact with the floor surface.

The incremental position encoder (194) is responsible for monitoring motor movement by encoding motor rotations. The wheel moves by rotation as the motor drives by rotation. Therefore, determining motor movement by encoding motor rotations directly corresponds to measuring the length of a portion of a wheel, which has been brought into contact with the floor surface. By measuring counting encoding motor rotations, Gordon et al. is effectively determining the distance moved from the reference position (see column 10, lines 60 – 69; and column 11, lines 1 – 4).

10.   As for **Claim 3**, Gordon et al. disclose, that the moving pedestal is comprised of three wheels wherein each wheel is provided with a wheel angle encoder (194). The wheel angle

encoders (194) provide data to the microprocessor (180), wherein the microprocessor (180)

continuously subtracts the current positional data (including the position and rotation angle of the

moving pedestal) from target positional data to obtain a position error signal. Therefore, the

rotation angle is calculated based upon the moving distances of all three wheels, which includes

two wheels that are distant from each other in terms of a moving direction. In fact, since each of

the three wheels are at a separate vertex of an equilateral triangle making up the base of the

moving pedestal each two wheels will be distant from each other and the third in any given

moving direction.

11.   As for **Claim 4**, Gordon et al. as stated above since each of the three wheels are at a

separate vertex of an equilateral triangle making up the base of the moving pedestal each two

wheels will be distant from each other and the third in any given moving direction. Moreover,

all three wheels are equidistant from each other; thus, at least two wheels will always be most

distant.

12.   As for **Claim 5**, Gordon et al. disclose, as shown in figures 1A and 5A – 5F, wherein a

first line and a second line are provided (Y and X) on the floor surface to perpendicularly

intersect at said reference position (initial target 20),

        wherein two first sensors (B and C) for detecting the first line (Y; see figure 5A) and one

second sensor (A; see figure 5B) for detecting the second line are provided on the moving

pedestal (all sensors 18 are provided therein), and

        wherein said reference position and said reference angle are found based on a position of

each of the two first sensors at a time when the two first sensor each pass said first line, and a

position of the second sensor at a time when said second passes the second (When the sensors

begin to move from the initial target 20, the encoders begin to determine a moving amount.).

13.   For **Claim 6**, Gordon et al. disclose, as shown in figures 1C, 2, 5A – 5F, 7, and 8 and as

stated in columns 4 (lines 10 – 64), 5 (lines 36 – 58), 6 (lines 31 – 37), 7 (lines 50 – 66), 10 (lines

39 – 68), 11 (lines 1 – 4), and 12 (lines 16 – 37), an image pick-up system for picking up a real

object image of an object, comprising:

a camera unit (camera 48) comprising a camera for picking up an image of an object

mounted on a moving pedestal (12);

an calculating means (microprocessor 180) for calculating a positional relationship

between the camera and the object (see column 4, lines 27 – 30; column 10, lines 64 – 69; and

column 11, lines 1 – 4);

a setting means (microprocessor 180) for setting a reference position (initial encoder

count from incremental position encoder 194) on a floor surface on which the moving pedestal

moves and a reference angle (initial encoder count from wheel angle encoder 192) of said

moving pedestal (see column 6, lines 17 – 24 and 31 – 34) and for inputting the reference postion

and the reference angle to said calculating means (180);

a detection means (encoders 192 and 194) for detecting a moving amount of the moving

pedestal from the reference position, and a rotation angle of the moving pedestal from the

reference angle (see column 10, lines 39 – 69; and column 11, lines 1 – 4);

wherein said calculating means (microprocessor 180) calculates out a position and an

angle of the camera with respect to the object based on of the reference position, the reference

angle, the moving amount and the rotation angle of said moving pedestal (all of the above factors

are used by the microprocessor 180 to calculate a "position error signal" used to produce an

appropriate motor velocity for the motors of the moving pedestal), and the calculating means

transmits data of the position and the angle of the camera with respect to the object to a computer

for creating an image containing a real object image of the object taken with the camera (see

column 10, lines 64 – 68; column 11, lines 1 – 4; and column 12, lines 16 – 37).

Gordon et al. clearly disclose transmitting data of the position and the angle of the camera

with respect to the object to a computer for creating an image containing a real object image of

the object taken with the camera; however, Gordon et al. do not disclose an image pick-up

system for operating together a real object image of an object taken with the camera and another

image or a computer for operating together the real object image of the object taken with the

camera and said another image based on the position and the angle of the camera with respect to

the object.

On the other hand, Fellous also disclose an image pick-up system for capturing images of

an object with a camera mounted on a moving pedestal. More specifically, Fellous teach, as

shown in figures 1 and 2 and as stated in columns 5 (lines 3 – 23, 31 – 49, and 59 – 67), 6 (lines

6 – 25, 34 – 39, and 49 – 53), 7 (lines 1 – 18), an image pick-up method for capturing images of

an object (24 and 13) with a camera (2) mounted on a moving pedestal (5) and for operating

together (via computer 11) a real object image ("real images generated by the camera 2") of an

object taken with the camera ("fine-lined rectangle 24") and another image ("synthetic image"

shown on monitor 12), wherein a computer (11) is provided for operating together ("create a

hybrid combined image" – see column 5, lines 18 – 27) the real object image ("real images") of

the object taken with the camera (2) and said another image ("synthetic images") based on the

position and the angle of the camera with respect to the object ("geometrical coherence" – see column 6, line 54 – column 7, line 15).

As stated in column 2 (lines 1 – 25) of Fellous, at the time the invention was made, it would have been obvious to one with ordinary skill in the art to have provided a computer for operating together the real object image of the object taken with the camera and said another image based on the position and the angle of the camera with respect to the object as taught by Fellous, in the image pick-up system including a camera mounted on a pedestal disclosed by Gordon et al., for the following advantages: facilitating easy determination in a host computer of a parametric model of a real camera analogous to a virtual camera, providing real control of a virtual camera by a real camera, securing perfect coherence between a real image and a virtual image, and permitting a free combination of real images and geometrically coherent synthetic images.

14.   As for **Claim 7**, Gordon et al. disclose, wherein said setting means (microprocessor 180) includes a reference detection mechanism (optosensors 18) for detecting the reference position on the floor surface on which the move pedestal moves and the reference angle of the moving pedestal (initial target 20).

The setting means (microprocessor 180) sets a reference position (initial encoder count from incremental position encoder 194) and the reference angle (initial encoder count from wheel angle encoder 192).

15.   As for **Claim 8**, Gordon et al. disclose wherein said detection means detects the moving amount of the moving pedestal by measuring a length of a portion of a wheel of the moving pedestal, which has been brought into contact with the floor surface. The incremental position

encoder (194) is responsible for monitoring motor movement by encoding motor rotations. The

wheel moves as the motor moves. Therefore, determining motor movement by encoding motor

rotations directly corresponds to measuring the length of a portion of a wheel, which has been

brought into contact with the floor surface. By measuring a length, Gordon et al. is determining

the distance moved from the reference position (see column 10, lines 60 – 69; and column 11,

lines 1 – 4).

16.   As for **Claim 9**, Gordon et al. disclose, as shown in figures 1A, 1C, and 8, the moving

pedestal (dolly 12) comprises three wheels (three identical wheel assemblies 30/42); wherein

three encoders (wheel angle encoder 192) are respectively provided for the three wheels (see

column 10, lines 50 – 56) for detecting a moving distance of a respective one the wheels (see

column 10, lines 60 – 69; and column 11, lines 1 – 4).

17.   As for **Claim 10**, Gordon et al. disclose, that the moving pedestal is comprised of three

wheels wherein each wheel is provided with a wheel angle encoder (194). The wheel angle

encoders (194) provide data to the microprocessor (180), wherein the microprocessor (180)

continuously subtracts the current positional data (including the position and rotation angle of the

moving pedestal) from target positional data to obtain a position error signal. Therefore, the

rotation angle is calculated based upon the moving distances of all three wheels, which includes

two wheels that are distant from each other in terms of a moving direction. In fact, since each of

the three wheels are at a separate vertex of an equilateral triangle making up the base of the

moving pedestal each two wheels will be distant from each other and the third in any given

moving direction.

18.   As for **Claim 11**, Gordon et al. disclose, Gordon et al. as stated above since each of the

three wheels are at a separate vertex of an equilateral triangle making up the base of the moving

pedestal each two wheels will be distant from each other and the third in any given moving

direction. Moreover, all three wheels are equidistant from each other; thus, at least two wheels

will always be most distant.

19.   For **Claim 13**, Gordon et al. disclose, as shown in figures 1C, 2, 5A – 5F, 7, and 8 and as

stated in columns 4 (lines 10 – 64), 5 (lines 36 – 58), 6 (lines 31 – 37), 7 (lines 50 – 66), 10 (lines

39 – 68), 11 (lines 1 – 4), and 12 (lines 16 – 37), an image pick-up system for picking up an

image of an object, comprising:

a moving pedestal (dolly 12) including three wheels (three identical wheel assemblies

30/42);

a camera unit (camera 48) having a structure in which a camera for picking up an image

of an object, is mounted via a pan head (rotatable camera head 48) on said moving pedestal (12);

an operation means (microprocessor 180) for calculating a positional relationship

between the camera and the object (see column 4, lines 27 – 30; column 10, lines 64 – 69; and

column 11, lines 1 – 4);

three encoders (wheel angle encoder 192) provided respectively for said three wheels of

said moving pedestal (see column 10, lines 50 – 56);

a plurality of sensors (optosensors 18) provided on said moving pedestal (12), for

detecting a predetermined mark (targets 20) made on a floor surface ("studio floor") on which

said moving pedestal (12) moves; and

a setting means (microprocessor 180) for setting a reference position (initial encoder

count from incremental position encoder 194) on the floor surface, and a reference angle (initial

encoder count from wheel angle encoder 192) of said moving pedestal, which are found from

detection values of said plurality of sensors (18; detects that the moving pedestal is at an "initial

target 20") and a pulse numbers counted by said encoders in the movement of said moving

pedestal, to said operation means (see column 6, lines 17 – 24 and 31 – 34);

wherein said operation means (microprocessor 180) calculates out a position and an angle

of the camera with respect to the object on the basis of the reference position, the reference

angle, the moving amount and the rotation angle of said moving pedestal (all of the above factors

are used by the microprocessor 180 to calculate a "position error signal" used to produce an

appropriate motor velocity for the motors of the moving pedestal), which are obtained from the

pulse numbers counted by said encoders, and transmits data of the position and the angle of the

camera with respect to the object, to a computer for creating an image containing a real object

image of the object taken with the camera (see column 10, lines 64 – 68; column 11, lines 1 – 4;

and column 12, lines 16 – 37).

Gordon et al. clearly disclose transmitting data of the position and the angle of the camera

with respect to the object to a computer for creating an image containing a real object image of

the object taken with the camera; however, Gordon et al. do not disclose an image pick-up

system for operating together a real object image of an object taken with the camera and another

image or a computer for operating together the real object image of the object taken with the

camera and said another image based on the position and the angle of the camera with respect to

the object.

On the other hand, Fellous also disclose an image pick-up system for capturing images of an object with a camera mounted on a moving pedestal. More specifically, Fellous teach, as shown in figures 1 and 2 and as stated in columns 5 (lines 3 – 23, 31 – 49, and 59 – 67), 6 (lines 6 – 25, 34 – 39, and 49 – 53), 7 (lines 1 – 18), an image pick-up method for capturing images of an object (24 and 13) with a camera (2) mounted on a moving pedestal (5) and for operating together (via computer 11) a real object image ("real images generated by the camera 2") of an object taken with the camera ("fine-lined rectangle 24") and another image ("synthetic image" shown on monitor 12), wherein a computer (11) is provided for operating together ("create a hybrid combined image" – see column 5, lines 18 – 27) the real object image ("real images") of the object taken with the camera (2) and said another image ("synthetic images") based on the position and the angle of the camera with respect to the object ("geometrical coherence" – see column 6, line 54 – column 7, line 15).

As stated in column 2 (lines 1 – 25) of Fellous, at the time the invention was made, it would have been obvious to one with ordinary skill in the art to have provided a computer for operating together the real object image of the object taken with the camera and said another image based on the position and the angle of the camera with respect to the object as taught by Fellous, in the image pick-up system including a camera mounted on a pedestal disclosed by Gordon et al., for the following advantages: facilitating easy determination in a host computer of a parametric model of a real camera analogous to a virtual camera, providing real control of a virtual camera by a real camera, securing perfect coherence between a real image and a virtual image, and permitting a free combination of real images and geometrically coherent synthetic images.

Allowable Subject Matter

20.   **Claim 12** is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

21.   As for **Claim 12**, while the prior art simply disclose of a wheel angle encoder connected to the wheel for determining the rotation angle of the wheel and an incremental position encoder connected to a motor for determining the distance traveled in a moving direction of the moving pedestal; the closest prior art does not teach or fairly suggest wherein rollers are provided as being brought into contact with the wheels, respectively, to be rotated along with the rotation of the wheels, and the moving distance of each of the wheels is found from the number of rotation of the respective roller and a pulse number counted by said respective encoder.

Cited Prior Art

22.   The prior art made of record and not relied upon is considered pertinent to Applicant's disclosure each discloses an image pickup system and corresponding method including a mounted camera for capturing real images relative to a camera position for combination with virtual images generated relative to the camera position.

Conclusion

23.   Applicant's amendment necessitated the new ground(s) of rejection presented in this

Office action. Accordingly, **THIS ACTION IS MADE FINAL.** See MPEP § 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within TWO

MONTHS of the mailing date of this final action and the advisory action is not mailed until after

the end of the THREE-MONTH shortened statutory period, then the shortened statutory period

will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

however, will the statutory period for reply expire later than SIX MONTHS from the date of this

final action.

Any inquiry concerning this communication or earlier communications from the

Examiner should be directed to Justin P Misleh whose telephone number is 571.272.7313. The

Examiner can normally be reached on Monday through Thursday from 7:30 AM to 5:00 PM and

on alternating Fridays from 8:00 AM to 4:30 PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's

supervisor, Wendy R Garber can be reached on 571.272.7308. The fax phone number for the

organization where this application or proceeding is assigned is 703.872.9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JPM
April 22, 2005

WENDY R. GARBER
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600